



M/V Pacific Valour

- ▶ **Bollard Pull** 110-126 tonnes
- ▶ **Brake Horsepower** 8807 BHP
- ▶ **Clear Deck Space** 365-416 m²
- ▶ **Winch Line Pull** 255 tonnes

M/V Pacific Valour

Bollard Pull	110-126 tonnes	Brake Horsepower	8807 BHP
Clear Deck Space	365-416 m ²	Winch Line Pull	255 tonnes

General Information

Built:	Labroy shipyard, Batam, December 2009
IMO No.:	9443516
Classification:	DNV-GL +1A Fire fighter(I) Offshore service vessel(Anchor handling, Towing) DPS(2) E0

Dimensions

Length, overall:	66.0 metres
Length, BP:	57.0 metres
Breadth, moulded:	16.0 metres
Depth, main deck:	7.3 metres
Maximum draft midship:	6.2 metres
GT:	2147
NT:	644

Capacities

Deadweight (maximum):	2452 tonnes
Clear Deck Area:	416 m ² (32.5 x 12.8 m)
Deck Strength:	5t/m ²
Deck Cargo:	870 tonnes
Fuel:	810.42 m ³ (dedicated) 1275.06 m ³ (including the combined use Mud/Brine tanks)
Potable Water:	455 m ³
Ballast Water:	931 m ³
Brine / DMA / Glycol / Liquid	125 m ³ (in 2 dedicated tanks)
Mud:	589 m ³ (including the combined use Mud tanks - s.g. of 2.5)
Liquid Mud:	465 m ³ (in 6 dedicated tanks) 589 m ³ (including the combined use Brine tanks - s.g. of 2.5)
Dry Bulk:	185 m ³ (approximately 6600 cubic feet) total capacity in 4 tanks
Ship's Stores:	Freezer (-25 degrees Celsius) - approximately 12 m ³ Cooler (+4 degrees Celsius) - approximately 12 m ³ Dry Stores - approximately 26 m ³

Machinery

Main Engines:	2 x 3285 kW = 6570 kW (8807 BHP) MAN B&W 9L27/38
Propulsion:	2 x MAN B&W Alpha CPP Propellers in MAN AHT Kort nozzles
Bow Thrusters:	2 x 600 kW = 1200 kW (1608 BHP) Brunvoll Tunnel Thrusters, approximately 9.0 tonnes thrust each
Stern Thrusters:	2 x 600 kW = 1200 kW (1608 BHP) Brunvoll Tunnel Thrusters, approximately 9.0 tonnes thrust
Shaft Generators:	2 x Leroy Somer shaft generators, 1300 kW, 1600 kVA each, 440 V, 60 Hz
Auxiliary Generators:	1 x Caterpillar 3406 Diesel Generator, 270 kW, 440 V, 60 Hz
Emergency Generators:	1 x air cooled Caterpillar 3406 Diesel Generator, 270 kW, 440 V, 60 Hz

M/V Pacific Valour

Bollard Pull	110-126 tonnes	Brake Horsepower	8807 BHP
Clear Deck Space	365-416 m ²	Winch Line Pull	255 tonnes

Towing and Anchor Handling

Bollard Pull:	110.29 MT @ 100% MCR
Main Winch:	1 x Hydrakraft 250 tonne variable pressure waterfall winch
Load Capacity:	Towing and Anchor Handling Drums: Pulling Force - 1st layer - 255 tonnes, mid layer - 165 tonnes, outer layer - 122 tonnes (low speed) Pulling Speed - 1st layer - 11.4 m/min, mid layer - 17.6 m/min, outer layer - 23.8 m/min (low speed) Pulling force - 1st layer - 127 tonnes, mid layer - 82 tonnes, outer layer - 61 tonnes (high speed) Pulling speed - 1st layer - 22.8 m/min, mid layer - 35.2 m/min, outer layer - 47.6 m/min (high speed) The Anchor Handling Drum and Towing Drum are capable of 250 tonnes pull on 1st layer simultaneously
Brake Capacity:	Brake Force: 1st layer - 320 tonnes mid layer - 207 tonnes outer layer - 153 tonnes
Tow Drum Wire Capacity:	1500 m x 71 mm diameter
Work Drum Capacity:	1500 m x 71 mm diameter
Chain Gypsy Cable Lifter:	1 x 76 mm, 1 x 84 mm mounted on each side of anchor handling drum
Rig Chain Locker:	195 m ³ chain capacity
Stern Roller:	Rolls Royce, SWL 350 tonnes, 5.5 m x 2.0 m diameter
Tow Pins / Guide Pins:	1 pair of retractable Karmoy guide pins with horizontal locking tops
Wire Chain Stopper:	2 x retractable Karm forks, SWL 300 tonnes for wire/chain up to 102 mm
Spare Reel Capacity:	1 x Hydrakraft variable pressure, 20 tonnes pull on 1st layer, 1400 m x 71 mm diameter
Pennant Storage Reels:	2 x Hydrakraft variable pressure, 20 tonnes pull on 1st layer, 1000 m x 76 mm diameter

Deck Machinery

Tuggers:	2 x 10 tonnes Hydrakraft
Capstans:	2 x 16 tonne (warping head) / 10 tonne (wire drum) Hydrakraft
Windlass:	1 x 10 tonne Hydrakraft, 2100 kg anchors with 440 m x 36 mm chain each side
Bow Mooring:	2 x mooring drums, capacity of 200 m x 56 mm rope each
Smit Towing Bracket:	1 x 200 tonnes SWL located on the Forecastle
Crane Capacity:	TTS, 5 tonnes at 13 m radius

Electronics

Main Radar:	1 x Furuno FAR-2117 X Band ARPA Radar with 21" LCD display
Auxiliary Radar:	1 x Furuno FAR-2137S S Band ARPA Radar with 21" LCD display
Auto Pilot:	1 x Tokimec PR 6000 Series
Gyro Compass:	3 x Tokimec TG8000 with repeaters in wheelhouse and steering gear room
Magnetic Compass:	1 x Cassen & Plath REFLECTA 1
Echo Sounder:	1 x Skipper GDS102, Dual Frequency, 1500 m water depth

M/V Pacific Valour

Bollard Pull	110-126 tonnes	Brake Horsepower	8807 BHP
Clear Deck Space	365-416 m ²	Winch Line Pull	255 tonnes

DGPS :	2 x Veripos LD3 – G1 GPS: 1 x Furuno GP-150
Anemometer :	3 x Gill ultrasonic units + 1 x Young Windtracker
Speed Log:	1 x Furuno DS-80 Doppler Speed log
Communications:	1 x Furuno G.M.D.S.S. (Global Maritime Distress & Safety System) Area A3 set 1 x Sailor CU5100 (250W) MF/HF Radio 1 x Furuno FM-8800S (25W) VHF DSC 1 x Furuno FM-8800D (25W) VHF DSC 1 x Furuno FELCOM-15 Inmarsat-C 1 x Furuno FELCOM-15 Inmarsat-C/SSAS 1 x Furuno NX-700B Navtex Receiver 3 x McMurdo Portable GMDSS VHF Radios 1 x McMurdo EPIRB 2 x McMurdo SART 1 x Sailor cu 5100 MF/HF Rado
Weather Fax:	1 x Furuno
Satellite Communication:	FBB: Sailor 500
AIS:	1 x Furuno FA-150

Discharge Pumps

Fuel Oil:	1 x 100 m ³ /hr - 7.0 bar
Potable Water:	1 x 150 m ³ /hr - 7.0 bar
Drill Water:	1 x 150 m ³ /hr - 7.0 bar
Liquid Mud:	1 x 75 m ³ /hr - 18.0 bar
Brine / Mud:	1 x 75 m ³ /hr - 18.0 bar
Dry Bulk:	80 cbm/hr - 5.6 bar (2 compressors)
Cargo Flow Meters :	Fuel Oil and Potable Water
Hose Connections :	Fuel - 4" (Camlock OR Drybreak) Potable Water - 4" (Camlock) Drill Water - 4" (Camlock) Mud - 5" (Camlock) Brine - 5" (Camlock) Dry Bulk - 5" (Camlock) Adapters 5" to 4" reducer, 4" to 3" reducer

Performance

Speed / Fuel Consumption:	At 100% MCR, approximate consumption is 34 tonnes / day Economical speed 10-12 knots, approximate consumption is 12 tonnes / day Idle at sea: approximate consumption 4 tonnes / day Idle in port: approximate consumption 0.8 tonnes / day
---------------------------	--

Dynamic Positioning

Type:	GE ADP02
Reference Systems:	1 x Fanbeam complete with 2 reflectors, 2 x Veripos LD5 DGPS

M/V Pacific Valour

Bollard Pull	110-126 tonnes	Brake Horsepower	8807 BHP
Clear Deck Space	365-416 m ²	Winch Line Pull	255 tonnes

Control Modes: Joystick manual heading, Joystick auto heading, Dynamic Positioning, Model Control (dead reckoning), DP minimum power, Ship follow, Auto track, Auto Pilot, Auto Sail, ROV follow, Simulation (for training purposes)

External Fire Fighting

Capacity: 2 x 1500 m³/hr = 3000 m³/hr
Monitors: 2 x 1200 m³/hr, Kvaerner, each fitted on wheelhouse top and remotely controlled from within the wheelhouse
Throw Length: 120 m
Throw Height: 50 m
Drenching System: with 4 hose manifold each side – aft.

Standby Rescue Equipment

1. 1 x Maritime Partner MP660 Springer, 10 persons, SOLAS approved FRB with inboard diesel waterjet.
2. Rescue Zones on both Port and Starboard side of main deck, with scramble nets and personnel transfer swing ropes

Anti-Pollution

Dispersant Tank: 9.64 m³
Dispersant nozzles: each with a 1 1/4" nozzle & a 3/4" nozzle

Accommodation

Berths: 8 x single cabins
4 x 2 man cabins (including hospital)
4 x 4 man cabins
1 x Library
1 x Messroom
1 x Lounge

Environmental Features

1. Mud tank of free flowing design with external stiffening, sloped floors and dedicated recirculation
2. Low residue design bulk tanks
3. 1 x oily water separator with 15 ppm monitor. Compliant with IMO - Resolution MEPC 107(49)
4. 1 x sewage treatment plant
5. Galley macerator
6. Cargo load/discharge station with save all to inboard tank

M/V Pacific Valour

Bollard Pull	110-126 tonnes	Brake Horsepower	8807 BHP
Clear Deck Space	365-416 m2	Winch Line Pull	255 tonnes

Miscellaneous

1. Design complies to latest rules and regulations from SOLAS 74, with amendments in force and IMO 469 (XII) "Guidelines for the design and construction of offshore supply vessel"
2. Fresh water ultra violet steriliser
3. Fitted with 2 x Halogen searchlights, each 2000 W, fitted on the wheelhouse top and remotely controlled from inside the wheelhouse
4. Fitted with 6 x 1000 W high pressure sodium lights for the aft deck cargo area and 2 x 1000 W high pressure sodium lights in the crash rails to illuminate Anchor Handling area
5. Removable section of crash rail, 6 m long, on Port and Starboard side forward to allow for fitting of ROV spread, etc
6. Wood sheathed main deck except for the aft area, which is steel plated for Anchor Handling
7. Welding and cutting equipment and lathe in workshop
8. Flume passive roll damping system
9. Fire detection system fitted to the accommodation, all store rooms and machinery spaces throughout the vessel
10. CO2 fixed fire extinguishing system for Machinery Space, Emergency Generator Room, Paint Locker and Hydraulic Pump Room
11. Local water spray Fire Fighting system according to SOLAS regulations
12. Statutory liferafts, life-jackets and pyrotechnics
13. Deck power supplies for ROV equipment / Charterer's equipment:
 - 2 x 500A, 440V, 3ph
 - 1 x 63A, 440V, 3ph
 - 1 x 32A, 440V, 3ph
14. Deck power supplies for Refrigerated containers:
 - 6 x 440V, 63A, 3ph
15. DRAGER PAS Colt Airline and Escape Trolley Unit for tank rescue
16. Protector bulk tank cleaning air hoods and lines
17. RO-Water Maker 10 m3/per day (Cathelco seafresh)